

TC4017BP, TC4017BF

TC4017BP/TC4017BF DECADE COUNTER/DIVIDER

TC4017BP/BF is decimal Johnson counter consisting of 5 stage D-type flip-flop equipped with the decoder to convert the output to decimal.



Depending on the number of count pulses fed to CLOCK or CLOCK INHIBIT one output among 10 output lines "Q0" through "Q9" becomes "H" level.

The counter advances its state at rising edge of CLOCK (CLOCK INHIBIT="L") or falling edge of CLOCK INHIBIT (CLOCK="H"). RESET input to "H" level resets the counter to Q0="H" and Q1 through Q9="L" regardless of CLOCK and CLOCK INHIBIT.


MAXIMUM RATINGS

CHARACTERISTIC	SYMBOL	RATING	UNIT
DC Supply Voltage	V_{DD}	$V_{SS} - 0.5 \sim V_{SS} + 20$	V
Input Voltage	V_{IN}	$V_{SS} - 0.5 \sim V_{DD} + 0.5$	V
Output Voltage	V_{OUT}	$V_{SS} - 0.5 \sim V_{DD} + 0.5$	V
DC Input Current	I_{IN}	± 10	mA
Power Dissipation	P_D	300 (DIP) / 180 (SOIC)	mW
Operating Ambient Temperature Range	T_{opr}	$-40 \sim 85$	$^{\circ}\text{C}$
Storage Temperature Range	T_{stg}	$-65 \sim 150$	$^{\circ}\text{C}$

LOGIC DIAGRAM




P (DIP16-P-300-2.54A)
Weight : 1.00g (Typ.)



F (SOP16-P-300-1.27)
Weight : 0.18g (Typ.)

PIN ASSIGNMENT



TRUTH TABLE

INPUTS			SELECTED OUTPUT
CLOCK△	CLOCK INHIBIT△	RESET	
※	※	H	Q0
※	H	L	Qn (NC)
L	※	L	Qn (NC)
	L	L	Qn + 1
	L	L	Qn (NC)
H		L	Qn (NC)
H		L	Qn + 1

△ ; Level Change


※ ; Don't Care

NC ; No Change

CARRY OUT { "H" Q0 ~ Q4 = "H"

"L" Q5 ~ Q9 = "H"

TIMING CHART



RECOMMENDED OPERATING CONDITIONS (V_{SS} = 0V)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
DC Supply Voltage	V _{DD}		3	—	18	V
Input Voltage	V _{IN}		0	—	V _{DD}	V

STATIC ELECTRICAL CHARACTERISTICS (V_{SS} = 0V)

CHARACTERISTIC	SYM-BOL	TEST CONDITION	V _{DD} (V)	−40°C		25°C			85°C		UNIT
				MIN.	MAX.	MIN.	MIN.	MAX.	MIN.	MAX.	
High-Level Output Voltage	V _{OH}	I _{OUT} < 1μA V _{IN} = V _{SS} , V _{DD}	5	4.95	—	4.95	5.00	—	4.95	—	V
			10	9.95	—	9.95	10.00	—	9.95	—	
			15	14.95	—	14.95	15.00	—	14.95	—	
Low-Level Output Voltage	V _{OL}	I _{OUT} < 1μA V _{IN} = V _{SS} , V _{DD}	5	—	0.05	—	0.00	0.05	—	0.05	
			10	—	0.05	—	0.00	0.05	—	0.05	
			15	—	0.05	—	0.00	0.05	—	0.05	

STATIC ELECTRICAL CHARACTERISTICS (V_{SS} = 0V)

CHARACTERISTIC	SYM-BOL	TEST CONDITION	V _{DD} (V)	- 40°C		25°C			85°C		UNIT
				MIN.	MAX.	MIN.	MIN.	MAX.	MIN.	MAX.	
Output High Current	I _{OH}	V _{OH} = 4.6V	5	-0.61	—	-0.51	-1.0	—	-0.42	—	mA
		V _{OH} = 2.5V	5	-2.50	—	-2.10	-4.0	—	-1.70	—	
		V _{OH} = 9.5V	10	-1.50	—	-1.30	-2.2	—	-1.10	—	
		V _{OH} = 13.5V	15	-4.00	—	-3.40	-9.0	—	-2.80	—	
		V _{IN} = V _{SS} , V _{DD}									
Output Low Current	I _{OL}	V _{OL} = 0.4V	5	0.61	—	0.51	1.5	—	0.42	—	mA
		V _{OL} = 0.5V	10	1.50	—	1.30	3.8	—	1.10	—	
		V _{OL} = 1.5V	15	4.00	—	3.40	15.0	—	2.80	—	
		V _{IN} = V _{SS} , V _{DD}									
		V _{IN} = V _{SS} , V _{DD}									
Input High Voltage	V _{IH}	V _{OUT} = 0.5V, 4.5V	5	3.5	—	3.5	2.75	—	3.5	—	V
		V _{OUT} = 1.0V, 9.0V	10	7.0	—	7.0	5.50	—	7.0	—	
		V _{OUT} = 1.5V, 13.5V	15	11.0	—	11.0	8.25	—	11.0	—	
		I _{OUT} < 1μA									
Input Low Voltage	V _{IL}	V _{OUT} = 0.5V, 4.5V	5	—	1.5	—	2.25	1.5	—	1.5	V
		V _{OUT} = 1.0V, 9.0V	10	—	3.0	—	4.50	3.0	—	3.0	
		V _{OUT} = 1.5V, 13.5V	15	—	4.0	—	6.75	4.0	—	4.0	
		I _{OUT} < 1μA									
Input Current	"H" Level	I _{IH}	V _{IH} = 18V	18	—	0.1	—	10 ⁻⁵	0.1	—	μA
	"L" Level	I _{IL}	V _{IL} = 0V	18	—	-0.1	—	-10 ⁻⁵	-0.1	—	
Quiescent Supply Current	I _{DD}	V _{IN} = V _{SS} , V _{DD} *	5	—	5	—	0.005	5	—	150	μA
			10	—	10	—	0.010	10	—	300	
			15	—	15	—	0.015	20	—	600	

* All valid input combinations.

DYNAMIC ELECTRICAL CHARACTERISTICS (Ta = 25°C, V_{SS} = 0V, C_L = 50pF)


CHARACTERISTIC	SYMBOL	TEST CONDITION	V _{DD} (V)	MIN.	TYP.	MAX.	UNIT
Output Transition Time (Low to High)	t _{TLH}		5	—	80	200	ns
			10	—	50	100	
			15	—	40	80	
Output Transition Time (High to Low)	t _{THL}		5	—	80	200	
			10	—	50	100	
			15	—	40	80	

DYNAMIC ELECTRICAL CHARACTERISTICS (Ta = 25°C, Vss = 0V, CL = 50pF)


CHARACTERISTIC	SYMBOL	TEST CONDITION	V _{DD} (V)	MIN.	TYP.	MAX.	UNIT
Propagation Delay Time (CLOCK - Qn)	t _{pLH} t _{pHL}		5	—	325	650	ns
			10	—	135	270	
			15	—	85	170	
Propagation Delay Time (CLOCK - CARRY OUT)	t _{pLH} t _{pHL}		5	—	280	600	
			10	—	110	250	
			15	—	75	160	
Propagation Delay Time (RESET - Qn RESET - CARRY OUT)	t _{pLH} t _{pHL}		5	—	265	530	
			10	—	115	230	
			15	—	85	170	
Max. Clock Frequency	f _{CL}		5	2.5	6.0	—	MHz
			10	5.0	12.0	—	
			15	6.7	13.5	—	
Min. Clock Pulse Width	t _W		5	—	85	200	ns
			10	—	40	90	
			15	—	35	60	
Min. Pulse Width (RESET)	t _{WH}		5	—	50	260	
			10	—	20	110	
			15	—	15	60	
Max. Clock Rise Time Max. Clock Fall Time	t _{rCL} t _{fCL}		5 10 15	No Limit			μs
Min. Set-up Time (CLOCK INHIBIT - CLOCK)	t _{SU}		5	—	30	230	ns
			10	—	15	100	
			15	—	10	70	
Min. Removal Time (RESET - CLOCK)	t _{rem}		5	—	— 55	400	ns
			10	—	— 20	275	
			15	—	— 15	150	
Input Capacitance	C _{IN}			—	5	7.5	pF

WAVEFORMS FOR MEASUREMENT OF DYNAMIC CHARACTERISTICS


WAVEFORM 1.



WAVEFORM 2.




WAVEFORM 3.



DIP 16PIN PACKAGE DIMENSIONS (DIP16-P-300-2.54A)


Unit in mm



Weight : 1.00g (Typ.)

SOP 16PIN (200mil BODY) PACKAGE DIMENSIONS (SOP16-P-300-1.27)

Unit in mm



Weight : 0.18g (Typ.)

RESTRICTIONS ON PRODUCT USE

000707EBA

- TOSHIBA is continually working to improve the quality and reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to comply with the standards of safety in making a safe design for the entire system, and to avoid situations in which a malfunction or failure of such TOSHIBA products could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent TOSHIBA products specifications. Also, please keep in mind the precautions and conditions set forth in the "Handling Guide for Semiconductor Devices," or "TOSHIBA Semiconductor Reliability Handbook" etc..
- The TOSHIBA products listed in this document are intended for usage in general electronics applications (computer, personal equipment, office equipment, measuring equipment, industrial robotics, domestic appliances, etc.). These TOSHIBA products are neither intended nor warranted for usage in equipment that requires extraordinarily high quality and/or reliability or a malfunction or failure of which may cause loss of human life or bodily injury ("Unintended Usage"). Unintended Usage include atomic energy control instruments, airplane or spaceship instruments, transportation instruments, traffic signal instruments, combustion control instruments, medical instruments, all types of safety devices, etc.. Unintended Usage of TOSHIBA products listed in this document shall be made at the customer's own risk.
- The products described in this document are subject to the foreign exchange and foreign trade laws.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.